


15A, 20A | Lev-Lok® Decora Plus™ Modular Receptacles | Hospital Grade

Lev-Lok® Decora Plus™ Extra Heavy-Duty Hospital Grade Modular Receptacles

Features and Benefits

- Constructed with impact-resistant thermoplastic nylon cover and body
- Smooth face prevents dirt from collecting
- Four corner latches securely fasten the receptacle's face to the body
- Large triple-wipe, brass "T" line contacts for superior contact and conductivity
- #12 AWG THHN wire leads, 6" length on MSTWL series wiring modules
- For isolated ground versions, device strap is zinc plated steel and isolated ground system is brass
- Grounding clip permanently secured to strap for easy, simple, and secure installation
- Wiring module locks and latches to the receptacle body providing double the connection security
- Receptacle to be installed only with Leviton MSTWL series wiring modules
- MSTWL wiring module shipped separately with protective label and factory-installed circuit ID label
- Backed by a limited 10-year warranty

M1636-HGW



Grounding clip permanently secured to strap makes for most reliable ground connection

Constructed with impact-resistant thermoplastic nylon cover and body

Smooth face prevents dirt from collecting and makes cleaning faster and simpler

Four corner latches securely fasten the receptacle's face to the body

Solid brass locking pins for strong, secure connection between receptacle and wiring module



Nickel-plated brass single-piece wrap-around mounting strap with integral ground contacts for continuous conductivity and secure ground path (on select models) Two latches

mate with





15A, 20A | Snap-In Devices

Snap-In Devices

Features and Benefits

- All 1306 products come with dual exiting capabilities
- Snap-in devices with other mounting clips and terminations available upon request

2-Wire Snap-In Devices									
Rating		15A-125V							
NEMA		1-15R							
Description	Colors	Cat. No. Receptacle	Cat. No. Plug	Panel Thickness (Inches)	Panel Opening (Inches)				
2-Wire Polarized Receptacle Leads #14 AWG, 105°C Plastic, 6" Long, Stripped ¹ / ₂ "	White Black	1306-W 1306	_	.028060 .028060	.97 x .52 .97 x .52				



1306-W

3-Wire Snap-In Devices							
Rating	15A-125V						
NEMA		5-15R	5-15P				
Description	Colors	Cat. No. Receptacle	Cat. No. Plug	Panel Thickness (Inches)	Panel Opening (Inches)		
3-Wire Grounding, Leads #14 AWG, 105°C Plastic, 6" Long, Stripped ¹ / ₂ ", Grounding Wire #16 AWG	White Black	1374-W 1374-1	_ 1373-1	.031080 .031080	.95 x 95 .95 x 95		



^{*}Other panel thicknesses available