



NON-METALLIC PIPE HANGERS, BRACKETS & BEAM CLAMPS

NON-METALLIC CABLE TRAY & STRUT SYSTEMS


CLEVIS HANGERS




Nominal Pipe Size		Cat. No.	Maximum O.D. Range		Hanger Rod	Design Load	
in.	mm		in.	mm	Size	lb.	N-m
2	50	NM-SCH200	2-1/2	63	1/2" - 13	90	0.40
2-1/2	65	NM-SCH212	3-1/4	82	1/2" - 13	120	0.54
3	80	NM-SCH300	3-7/8	98	1/2" - 13	160	0.71
4	100	NM-SCH400	5	127	5/8" - 11	250	1.12
6	150	NM-SCH600	7	177	5/8" - 11	400	1.79
8	200	NM-SCH800	9	228	5/8" - 11	450	2.01
10	250	NM-SCH1000	11-3/8	289	5/8" - 11	500	2.24
12	300	NM-SCH1200	13-1/2	342	5/8" - 11	600	2.69

Safety Factor of 3 on Design Loads at 120°F (49°C).
Insulation may be required at high temperatures.
Order hanger rods and nuts separately.

SUPPORT BRACKETS



SB 1




SB 2

Cat. No.*	Dimension "A"		Design Load	
	in.	mm	lb.	N
NM-SB1-06P	10	250	1400	6.22
NM-SB1-09P	13	330	1000	4.45
NM-SB1-12P	16	406	800	3.56
NM-SB1-18P	22	559	675	3.00
NM-SB1-24P	28	711	450	2.00
NM-SB2-24P	28	711	750	3.33
NM-SB2-30P	34	863	750	3.33
NM-SB2-36P	40	1016	750	3.33

*Substitute "V" for "P" when Vinyl Ester Resin is needed.
Design loads based on uniform loading with a Safety Factor of 3.

BEAM CLAMPS



Description	Cat. No.	Design Load	
		lb. / ft.	kg / m
Beam Clamp	NM-SBC	800	3.56
Beam Clamp w/retainer clip	NM-SBC-RC	800	3.56

Safety Factor of 3 on Design Load.